




**Art.-No.: YWDMA-LANS-2601-D**  
**LED luminaire "MAVS", ceiling surface mounting,**  
**rectangular, 850x59x79mm, 26W, 2750lm, 4000K, CRI**  
**>80, IP40, white, switchable**



LED ceiling- and wall-mounted luminaire, MAVS. Housing made from aluminium, white, powder-coated. Diffuser made from plastic (PMMA), opal, UV-stabilised. Operating unit can be switched or dimmed (DALI dimmer), integrated. Version with CASAMBI® Bluetooth control available. DC compatible.

## TECHNICAL DATA


Electrical data	
Input Voltage AC	AC 220-240V / 50-60Hz
Power Factor	0.9
System power	26 W
Inrush current	29 A
Inrush current duration	143 $\mu$ s
Luminaires on C16A fuse	42 Stk.
DC Ready	Yes
Connection cross section	2.5 mm <sup>2</sup>
Electrical version	with internal operating device, switchable
CASAMBI Ready	Yes
Photometrical data	
Light source	LED
Colour temperature	4,000 K
Rated luminous flux	2,750 lm
Luminous efficacy	106 lm/W
Light colour	840
Colour rendering index (CRI)	> 80
Colour tolerance	3
Beam angle	60 °
UGR	26.2
Lifetime (h, at 25°C)	75,000 h, L80



Acceptance tests	
Certifications	CE
Protection class	I
Ingress protection (IP) rating	IP 40
Ambient temperature	-20 to +30 C°
Physical data	
Mounting method	ceiling mounted
Housing material	Aluminium
Housing colour	silver
Cover material	PMMA
Length (L)	850 mm
Width (B)	59 mm
Height (H)	79 mm
Product weight	2 kg
Weight incl. Packaging	2.3 kg
Packaging Length (L)	1,300 mm
Packaging Width (B)	118 mm
Packaging Height (H)	75 mm



## LIGHT DISTRIBUTION



## ACCESSORIES

YWDMA-PENDEL - Pendant set for MAVS incl. transparent cable 3 x 1.5 mm<sup>2</sup>

YWDMA-MONKL-A - Mounting clamp for MAVS, surface mounting / 1 pc.

State: 25.02.2024 - Subject to technical changes